

Safety Data Sheet

prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 700 S BASE Revision Date: 22/03/2016

Product Name:STONCHEM SATURANT 700 S
BASE

Supercedes Date:

17/09/2014

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coatings - Industrial use.

1.3 Details of the supplier of the safety data sheet

Importer: None

Manufacturer: StonCor Africa (Pty.) Ltd.

8 Cresset Road

Midrand Industrial Park, Chloorkop

P.O. Box 2205 2001, Johannesburg South Africa

Regulatory / Technical Information:

+27 11 254 5500

Datasheet Produced by: Maritz, Rory - ehs@stoncor.com

1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (Inside US)

CHEMTREC +1 703 5273887 (Outside ÚS)

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
Allergic effects
Hazardous to the aquatic environment, Chronic, category 3
Eye Irritation, category 2
Flammable Liquid, category 3
Reproductive Toxicity, category 2
STOT, repeated exposure, category 1
STOT, single exposure, category 3, RTI
Skin Irritation, category 2

2.2 Label elements

Symbol(s) of Product





Signal Word

Danger

Named Chemicals on Label

Styrene

HAZARD STATEMENTS

Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.	
Allergic effects	EUH208	Contains cobalt 2-ethylhexanoate. May produce an allergic reaction.	
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.	
Eye Irritation, category 2	H319	Causes serious eye irritation.	
Flammable Liquid, category 3	H226	Flammable liquid and vapour.	
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.	
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.	
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.	
Skin Irritation, category 2	H315	Causes skin irritation.	
PRECAUTION PHRASES			
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
	P264	Wash hands thoroughly after handling.	
	P273	Avoid release to the environment.	
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.	
	P284	Wear respiratory protection.	
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.	
	P308+P313	IF exposed or concerned: Get medical advice/attention	
	P314	Get medical advice/attention if you feel unwell.	
	P332+313	If skin irritation occurs: Get medical advice/attention.	
	P403+233	Store in a well-ventilated place. Keep container tightly closed.	

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	Chemical Name	<u>%</u>
100-42-5	Styrene	50-75
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-1.0
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	0.1-1.0
91-66-7	N,N-diethylaniline	0.1-1.0

136-52-7 cobalt 2-ethylhexanoate 0.1-1.0

CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
100-42-5	GHS02-GHS07-GHS08	H226-304-315-319-332-335-361-372	0
64742-95-6	GHS02-GHS08-GHS09	H226-304-411	0
64742-82-1	GHS02-GHS07-GHS08-GHS09	H226-304-336-411	0
91-66-7	GHS06-GHS08-GHS09	H301-311-331-373-410	0
136-52-7	GHS07-GHS09	H317-400	1

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to eyes. Harmful in contact with skin and if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Flammable.

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(EU)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/ m3	LTEL mg/ m3	OEL Note
Styrene	100-42-5					
Solvent naphtha (petroleum), light arom.	64742-95-6					
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1					
N,N-diethylaniline	91-66-7					
cobalt 2-ethylhexanoate	136-52-7					

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter. Respirator with filter for organic vapor.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety goggles. Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Clear
Physical State Liquid

Odor Solvent Like
Odor threshold Not determined
pH Non aqueous
Melting point / freezing point (°C) Not determined

Boiling point/range (°C) 56 - N.D.

Flash Point, (°C)

Evaporation rate

Not determined

Flammability (solid, gas)

Not determined

Upper/lower flammability or explosive 999 - 0

limits

Vapour PressureNot determinedVapour densityNot determinedRelative density1.14 - 1.16

Solubility in / Miscibility with water Nil

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Not determined

Not determined

Viscosity

400 - 600 cps

Explosive properties

Not determined

Not determined

Not determined

9.2 Other information

VOC Content g/l: 57
Calculated grams of VOC per liter of coating product as applied.
Specific Gravity (g/cm3) 1.167

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No Information Inhalation LC50: No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50
100-42-5	Styrene	2650 mg/kg	>2000 mg/kg	2800 ppm, 4 h
64742-95-6	Solvent naphtha (petroleum), light arom.	4700 mg/kg, oral, rat	>2000 mg/kg	3670 ppm/8 hours, rat, inhalation

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information
No information
No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	<u>Chemical Name</u>	EC50 48hr	<u>IC50 72hr</u>	LC50 96hr
100-42-5	Styrene	4.7 mg/l	No information	4.08 mg/l
64742-95-6	Solvent naphtha (petroleum), light arom.	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	No information	No information	
91-66-7	N,N-diethylaniline	No information	No information	

136-52-7 cobalt 2-ethylhexanoate No information No information

13. Disposal Considerations

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

3269 14.1 UN number

14.2 UN proper shipping name Polyester Resin Kit No Information Technical name

14.3 Transport hazard class(es) N/A

> No Information Subsidiary shipping hazard

14.4 Packing group

No Information 14.5 Environmental hazards 14.6 Special precautions for user Not applicable EmS-No.: No Information 14.7 Transport in bulk according to Annex II Not applicable

of MARPOL 73/78 and the IBC code

15. Regulatory Information

Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: No Information

Danish MAL Code: No Information No Information **Sweden Product Registration Number:**

Norway Product Registration Number: No Information

No Information WGK Class:

15.2 **Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

Flammable liquid and vapour. H226 H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. Causes skin irritation. H315 H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410 Toxic to aquatic life with long lasting effects. H411

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark ESIS (The European Chemical Substances Information System), provided by the European Commission Joint Research Centre in Ispra, Italy

Annex VI of the EU Council Directive 67/548/EEC

Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation)

EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.